



## Clinch-On® CORNERBEAD COMPANY

### SUBMITTAL SHEET

## PAPER FACED TAPE-ON CORNERBEAD AND TRIMS

*(See separate Submittal Sheet for our Coated Metal Cornerbeads and Trims)*

**Description:** Clinch-On manufactures its paper faced tape-on cornerbeads and trims using the Company's proprietary steel coating technique, specially engineered paper and a paper-to-steel lamination process that eliminates delaminating. The length of our paper flanges and our paper knurling (embossing) technique gives you superior joint compound adhesion and maximum protection for a professionally finished corner. A summary of our paper faced tape-on profiles follow (see separate Submittal Sheet for our paper faced nail-on):

- **Square Cornerbead:** Available for 90° corners with 7/8" flange length and 135° corners with 5/8" flange length.
- **Square No-Bead Cornerbead:** Available for 90° corners with 7/8" flange length.
- **Square Jumbo Wide Cornerbead:** Available for 90° corners with 1" flange length.
- **Square Reduced-Bead Jumbo Wide Cornerbead:** Available for 90° corners with 1" flange length.
- **Square No-Bead Jumbo Wide Cornerbead:** Available for 90° corners with 1" flange length.
- **Square Uneven Leg Cornerbead:** Available for 90° corners with 1/2"-7/8" flange length.
- **Square Inside Cornerbead:** Available for 90° corners with 3/8" flange length.
- **Bullnose Cornerbead:** Available for 90° corners with 3/4" radius and 1/4" flange length or 90° corners with 1-1/2" radius and 5/16" flange length or 90° corners with 1/2" radius and 1/4" flange length or 135° corners with 3/4" radius and 3/16" flange length.
- **Bullnose Pup Cornerbead:** Available for 90° corners with 3/4" radius and 1/4" flange length.
- **L-Bead:** Available for 1/4", 3/8", 1/2", 5/8", 3/4", or 1" drywall.
- **L-No Bead:** Available for 1/4", 3/8", 1/2", 5/8", 3/4", or 1" drywall.
- **Bullnose Kerf:** Available with 3/4" radius or 1/2" radius.

**Advantages:** Clinch-On uses American made steel. The Clinch-On proprietary metal coating technique provides a highly corrosion resistant corner with superior joint compound adhesion and maximum protection. Our nose design requires less joint compound, and our paper knurling (embossing) technique creates superior adhesion. Our durable fiber specially engineered paper prevents balling (fuzzing) when sanding.

**Limitations:** This product was designed for interior use.

**Certification:** Clinch-on Paper Faced Tape-On Cornerbead and Trims meets or exceeds ASTM specification C-1047.

**Installation:** Install in accordance with ASTM standards. We recommend you apply drywall joint compound (all-purpose or taping compound) to the back of the cornerbead for the full length of the cornerbead. Then attach the cornerbead squarely over the trimmed drywall corner. Use your fingers to press the cornerbead onto the drywall for the full length of the cornerbead. Use a knife to remove excess joint compound and any air bubbles. After drying, sand the corner lightly as necessary. For our L-Bead and Bullnose Kerf trim only one flange is required to hold the trim firmly in place.

**Storage and Job Conditions:** Store in a dry place protected from moisture, bending or other damage. Protect from extreme cold and heat and direct sunlight.

**Submittal Approvals - Job Name:** \_\_\_\_\_

**Contractor:** \_\_\_\_\_ **Date:** \_\_\_\_\_